

SUPER TRAD 301 SO DIGIT



+973 17879130

+973 17879135

ak@Alkarrargroup.com










SUPER TRAD 301 " SO DIGIT

New semi-automatic hydraulic metal bandsawing machine equipped with operator's interface for quick visualization of functional information such as

- Piece-counter (programmable)
- Working hours (partial and total)
- Machine status
- Error messages
- Self diagnosis
- Selection to manual function and sawframe gravity downfeed
- Blade speed (optional). Made of massive iron castings for high performance on cutting sections up to 255mm diameter. New roundworking table "Plateau" providing precision mitering from 0° to 60° to the right and 45° to the left, protected against chips obtrusion and rust seizure

Accessories

- Rollerway on loading side L=2 mt (capacity 240 kg)
- Rollerway on unloading side L=2 mt with bar stop (capacity 240 kg)
- Rollerway on loading side L=2 mt (capacity 1000 kg)
- Rollerway on unloading side L=2 mt with bar stop (capacity 1000 kg)
- Inverter from 20 to 105 mt/min. variable blade speed
- Blade lubricant nebulizer

301		Mitering Angles				 2750*27*0.9 kW 1.1-1.4 rpm 33/66  305 mm  510 KG	 A=120cm B=200cm H=195cm	OPTIONAL  INVERTER
		0	45	45	60			
		225	160	200	110			
		250	160	190	110			
		300*220	190*100 150*170	190*170	110*130			

Electric motor Threephase	kW	1.0 - 1.4
Electropump	kW	0.11
Hydraulic pump motor	kW	0.4
Gearbox reduction ratio	l	40/1
Blade dimension	mm	2750x27x0.9
Flywheel diameter	mm	300
Blade speed	rpm	33-66
Vice opening	mm	305
Sawframe inclination	°	30
Working height	mm	940
Machine dimension	mm	1200x2000x1950
Machine weight	kg	510
Con Inverter With Inverter		
Electric motor	kW	1.5
Blade speed	rpm	20-105

