



ZIP 32 DA



+973 17879130

+973 17879135

ak@Alkarrargroup.com

ZIP 32 DA

New Bandsaws with DA Controlled Downfeed.

Thanks to DA device the cut can be effected automatically through sawframe downfeed at the speed controlled by a two functions “Push/Pull” type Thomas original hydraulic regulator. By Pushing the regulator, the sawframe will start its downfeed, whilst Pulling it stops it. At the end of the cut, both blade motor and electropump for coolant liquid will stop automatically. Miter sawing from 0° to 60° to the right and from 0° to 45° to the left. Gear-box in oil bath. Sawframe and vice in solid cast-iron. Gripswitch to start sawframe downfeed, blade motor and electropump simultaneously. Safety microswitches on blade cover and blade tension. Two blade speeds. Precision blade-guides with hard metals pads and adjustable bearings.

Accessories

- DA- Downfeed Assistance. Sawframe downfeed hydraulically controlled with variable feed rate accordi to the material to cut
- Rollerway on loading side L=2 mt (capacity 240 Kg)
- Rollerway on unloading side L=2 mt with bar-stop (capacity 240 Kg)
- Rollerway on loading side L=2 mt (capacity 1000 kg)
- Rollerway on unloading side L=2mt with bar stop (capacity 1000 kg)

Technical Data

Electric motor Threephase	kW	1.0 - 1.4
Electropump	kW	0.06
Gearbox reduction ratio	I	40/1
Blade dimension	mm	2750x27x0.9
Flywheel diameter	mm	300
Blade speed	rpm	40/70
Vice opening	mm	305
Sawframe inclination	°	30
Working height	mm	1030
Machine dimension	mm	1000x1800x1600
Machine weight	kg	285

32



	0	45	45	60
	225	160	200	110
	250	160	190	110
	300*220	130*100 150*170	190*170	110*130


2750*27*0.9

kW
1.1-1.4

rpm
40/70

305 mm

285 kg



A=100cm
B=180cm
H=160cm

OPTIONAL

DA